

MAGNETO-OPTICAL RECORDING/REPRODUCING SYSTEM MAGNETIC HEAD AND MAGNETO-OPTICAL RECORDING MEDIUM USED THEREFOR

Publication number: JP7176103 (A)

Publication date: 1995-07-14

Inventor(s): TACHIBANA SHINICHI +

Applicant(s): CANON KK +

Classification:

- international: G11B21/21; G11B5/02; G11B11/10; G11B11/105; G11B21/21; G11B5/02; G11B11/00; (IPC1-7): G11B21/21; G11B11/10; G11B5/02; G11B11/10

- European: G11B11/105D1; G11B11/105G4; G11B11/105M1

Application number: JP19930320291 19931220


Priority number(s): JP19930320291 19931220

Also published as:

EP0660317 (A2)
EP0660317 (A3)
EP0660317 (B1)
US5553037 (A)
DE69423315 (T2)

Abstract of JP 7176103 (A)

PURPOSE: To secure an excellent magnetic head floating traveling property and to attain excellent access and excellent recording/reproducing/erasing of information by suppressing the occurrence of adherence between a magnetic head and a magneto-optical disk in a magneto-optical recording/reproducing system. **CONSTITUTION:** The information is recorded on the magneto-optical disk 10 by floating and traveling the bottom surface of the magnetic head 14 on a protection film 13 formed on the surface of the magneto-optical disk 10. The surface roughness (alpha) of the bottom surface of the magnetic head 14 and the surface roughness (beta) of the protection film 13 of the magneto-optical disk 10 shown by a center line mean peak height (Rpm) satisfy the relational expression of $0.15 \leq (\alpha + \beta) \leq 1.0$. The surface roughness of the bottom surface of the magnetic head 14 is formed by the ruggedness provided with a directional property along the direction of relative movement for the magneto-optical disk 10.



Data supplied from the **espacenet** database — Worldwide